



3D-SCANNERS MILLING PROSTHETIC PARTS ORTHODONTICS

# Impressive versatility

for professional users

2



www.cadstar.dental

# **Boost** your efficiency – save 60% scanning time

# 12 seconds / 16 seconds (multi-die)

The new Integrated Pattern Generation Technology generates and processes the projected patterns directly in the optical head to achieve unrivaled scanning speed and makes the scanning process up to <u>60% faster.</u>



# Data you can trust!



0.09 0.08 0.07 0.06 0.05 0.04 0.03 0.02 0.01 - 0.01 - 0.02 - 0.03 - 0.04 - 0.05 - 0.06 - 0.07 - 0.08 - 0.09

#### 5 μm accuracy 2 μm repeatability



CADstar uses approved ISO standards for measuring and documenting the accuracy of all scanners. On top of that, the scanners are stress-tested in CADstar's dental production facility to achieve a perfect fit of all restoration types.

#### technical data

Height: 380 mm Width: 395 mm Depth: 335 mm <u>Weight</u>: 12 kg <u>Cameras</u>: 2x 2Mpx <u>Scan system</u>: 2-Axis Language: multilingual Connection type: USB 3.0 Power supply: 100-240V / 50-60 Hz Measurament volume: 120x60x60 mm Acquisition type: TRU color information Acquisition technology: structured white light





#### **Optical Status Indicator**

The OSI visually informs the user about the scanners current operating status.



### Deep acquisition strategies

Ability to look deeper into impressions or narrow areas, using our new PCT<sup>®</sup> technique and adapted scan strategies.



#### Automated impression axis

Thanks to the attachable 3<sup>rd</sup> Axis, you are able to scan double-sided or single tray impressions fully automatically.



High resolution

HR scan data with sharper edges and cleaner details.



White LED light source

To obtain as much scan data as possible, CS.Neo<sup>Pro</sup> uses the full spectrum of light.



Reliable results

Provided by a high precise glass calibration body and a calibration control system. Environmental sensors are giving feedback to the user when it's time for a recalibration.



TRU color

Hand-drawn color markings on the model are neatly and sharply captured, and prepared in Exocad for the design process. This function is especially helpful for the digital manufacturing of partial frameworks.

#### As you like it

You can choose out of 3 colors to get a perfect fit into your laboratory environment.

\* Classic

\* Manhattan Grey

\* All Black





# **Digitization has never been so easy**



Manual or automatic rescan function to gain even more scan data from hard to capture areas.




Get all new software updates automatically.

= Mers


Mesh



You got stuck? Get quick answers directly out of the scan application.



for hassle-free scanning and expert mode with more options and customizable scan strategies for advanced users.



Scan Triple Tray impressions in one step to speed up your workflow and increase the productivity in your lab.



Stop and Restart your work whenever you like. Don't start from scratch when you change your project during the scan.



Click-less workflow with full automatic alignment and automated work steps.



integration with Exocad and other  $3^{\rm rd}$  party CAD applications.



Manually export any scan data in all open file formats.

back



### Accessories

included



#### Arti-Base

The open construction of the CS.Neo<sup>Pro</sup> also enables the user to completely digitalise all common articulators with the aid of the Arti Base. The scanner automatically captures the entire vestibular area of the articulated models, and there is no annoying fixing of the upper and lower jaw.



#### **Calibration body**

The calibration body is part of the CS.Neo<sup>Pro</sup> recalibration system and allows recalibration of the system after vibrations or varying environmental conditions.



#### Multi Die Adapter

The Multi Die Adapter enables simultaneous capturing of up to 9 stumps with just one scan. This practical accessory means that the necessary scan time can be reduced and the economic efficiency of your device can be increased further.



## Model holder with screw

The model holder of the CS.Neo<sup>Pro</sup> keeps models at an ideal distance from the scanner and can also be upgraded with the model fixator.





#### Model fixator

Compatible with any model holder, model fixator provides a firm and reliable occlusion; fast and easy to use, can be applied on any case and will ensure a clear view of the buccal teeth profile.



#### Quarter Tray Adapter

With the Quarter Tray Adapter, partial models of upper and lower jaws, and up to four stumps, can be scanned simultaneously, which significantly increases the productivity of the scanning system. In just two scanning steps, the occlusion and subsequently the neighbouring teeth and stumps are captured.

# 2

# Automated impression axis

This attachable 3<sup>rd</sup> Axis with clip is able to mount single tray or triple tray impressions. Double sided impressions will be scanned on both sides during the acquisition process to capture upper jaw, lower jaw and the bite situation automatically.



## Model holder with blu tack

The model holder with blu tack can be included as default as well. It is an alternative to model holder with screw.



#### **Split Cast Adapter**

With the aid of the optional Split Case Adapter, bite registrations from common articulators can be transferred to the software automatically, correctly and with no loss of precision. We recommend this accessory above all for users of the following Exocad modules: Virtual Articulator, Splint Module. Adapters are compatible with:

- Artex / Adesso
  KaVo Protar
- Bioart A7
  Quicksplit
- Denar Mark2
  SAM

ITALY (int. sales)

Corso di porta vigentina 35 I-20122 Milano

#### AUSTRIA

Sparkassenstraße 4 5500 Bischofshofen

#### GERMANY

Unsöldstraße 2 80538 Munich

Tel. +43 (0) 6462 / 32 880 Fax +43 (0) 6462 / 60 11 11

office@cadstar.dental www.cadstar.dental

